

Firestone



REIFEN 380 / 85 R 30
135 D / 132 E, TL, PERFORMER 85
(14.9 R 30)

Product-No.: 10626285

Technical Information:

Tyre size	380 / 85 R 30
TL / TT	TL
LI / SI	135 D / 132 E
Tread	Performer 85
Manufacturer	Firestone
Recom. Rim	13
Permissible rim	11, 12
Width [mm]	406
Outer diameter [mm]	1405
Static radius [mm]	634
Rolling circumference [mm]	4215
Payload in kg at kph (1)	2180 / 65
Payload in kg at kph (2)	2000 / 70
Inflation pressure [bar]	1,60
Weight [Kg]	80,57
Tyre content 75% [litre]	210
Stud height [mm]	43,0
Number of studs	21x2
Zulassung	nicht notwendig
Direction bound	Yes

Hints and features:

- Standard tyre of the 85 series for mid-range tractors
- High load-bearing capacity
- Outstanding driving dynamics and road comfort owing to increased deflection
- Very good traction with low soil compaction due to patented dual angle tread blocks
- Very good self-cleaning properties
- Long service life and even wear

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.