Bohnenkamp Moving Professionals

Firestone



Hints and features:

- Agricultural tyre for high-performance tractors
- Very good traction in fields
- Excellent ride comfort on the road
- Very low soil compaction

REIFEN 650 / 85 R 38 173 D / 170 E, TL, MAXI TRACTION

Product-No.: 10626451

Technical Information:

Tyre size	650 / 85 R 38
TL / TT	TL
LI / SI	173 D / 170 E
Tread	Maxi Traction
Manufacturer	Firestone
Recom. Rim	23
Width [mm]	701
Outer diameter [mm]	2078
Static radius [mm]	940
Rolling circumference [mm]	6218
Payload in kg at kph (1)	6500 / 65
Payload in kg at kph (2)	6000 / 70
Inflation pressure [bar]	2,40
Weight [Kg]	333,4
Tyre content 75% [litre]	879
Stud height [mm]	63,0
Number of studs	21x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.