Bohnenkamp Moving Professionals

Firestone



Hints and features:

- Unique double-angle lug technology
- Large ground contact area due to stronger deflection and flatter tread pattern contour
- Increased ride comfort

REIFEN 480 / 70 R 24 138 D / 135 E, TL, PERFORMER 70

Product-No.: 10626645

Technical Information:

Tyre size	480 / 70 R 24
TL/TT	TL
LI / SI	138 D / 135 E
Tread	Performer 70
Manufacturer	Firestone
Recom. Rim	15
Permissible rim	14, 16
Width [mm]	482
Outer diameter [mm]	1323
Static radius [mm]	595
Rolling circumference [mm]	3969
Payload in kg at kph (1)	2360 / 65
Payload in kg at kph (2)	2180 / 70
Payload in kg at kph (2) Inflation pressure [bar]	2180 / 70 1,60
,	
Inflation pressure [bar]	1,60
Inflation pressure [bar] Weight [Kg]	1,60 98,8
Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre]	1,60 98,8 264
Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre] Stud height [mm]	1,60 98,8 264 46,5

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential

damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.