Bohnenkamp Moving Professionals

Firestone



Hints and features:

- Unique double-angle lug technology
- Large ground contact area due to stronger deflection and flatter tread pattern contour
- Increased ride comfort

REIFEN 520 / 70 R 38 150 D / 147 E, TL, PERFORMER 70

Product-No.: 10626765

Technical Information:

Tyre size	520 / 70 R 38
TL/TT	TL
LI / SI	150 D / 147 E
Tread	Performer 70
Manufacturer	Firestone
Recom. Rim	16
Permissible rim	15, 18
Width [mm]	523
Outer diameter [mm]	1777
Static radius [mm]	801
Rolling circumference [mm]	5331
Payload in kg at kph (1)	3350 / 65
Payload in kg at kph (2)	3075 / 70
Inflation pressure [bar]	1,60
Weight [Kg]	131,8
Tyre content 75% [litre]	444,75
Stud height [mm]	48,0
Number of studs	21x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential

damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.