# Bohnenkamp Moving Professionals

## Kleber



#### Hints and features:

- Maximum traction due to optimised lug shape
- Low soil compaction due to flat tread pattern
- Good ride comfort due to high deflection zone
- Long service life

## REIFEN 380 / 70 R 28 127 A8 / 127 B, TL, FITKER

## Product-No.: 12426285

### **Technical Information:**

Tyre size	380 / 70 R 28
TL / TT	TL
LI / SI	127 A8 / 127 B
Tread	Fitker
Manufacturer	Kleber
Recom. Rim	12
Permissible rim	11, 13
Width [mm]	392
Outer diameter [mm]	1308
Static radius [mm]	594
Rolling circumference [mm]	3881
Payload in kg at kph (1)	1750 / 40
Payload in kg at kph (2)	1750 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	68
Tyre content 75% [litre]	179
Stud width [mm]	30
Stud height [mm]	41,0
Number of studs	20x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.