

Kleber



■ ■ ● Bohnenkamp

REIFEN 210 / 95 R 32
114 A8 / 114 B**, TL, SUPER 3
(8.3 R 32)

Product-No.: 12426372

Technical Information:

Tyre size	210 / 95 R 32
TL / TT	TL
LI / SI	114 A8 / 114 B
Tread	Super 3
Manufacturer	Kleber
Recom. Rim	7
Width [mm]	212
Outer diameter [mm]	1212
Static radius [mm]	569
Rolling circumference [mm]	3638
Payload in kg at kph (1)	1180 / 40
Payload in kg at kph (2)	1180 / 50
Inflation pressure [bar]	2,40
Weight [Kg]	36,9
Tyre content 75% [litre]	67
Stud height [mm]	29,0
Number of studs	28x2
Zulassung	nicht notwendig
Direction bound	Yes

Hints and features:

- Row crop tyre for tractors within performance range of 80 - 200 hp
- Excellent growth of row crops: the lug shoulders protect plant stocks
- Robustness and service life: high load capacity. Even rolling of the tread lugs
- Time saving: for speeds of up to 50 km/h

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.