Bohnenkamp Moving Professionals

Kleber



Hints and features:

- Maximum traction due to optimised lug shape
- Low soil compaction due to flat tread pattern
- Good ride comfort due to high deflection zone
- Long service life

REIFEN 520 / 70 R 38 150 A8 / 150 B, TL, FITKER

Product-No.: 12426615

Technical Information:

Tyre size	520 / 70 R 38
TL/TT	TL
LI / SI	150 A8 / 150 B
Tread	Fitker
Manufacturer	Kleber
Recom. Rim	16
Permissible rim	15, 18
Width [mm]	536
Outer diameter [mm]	1765
Static radius [mm]	783
Rolling circumference [mm]	5228
Payload in kg at kph (1)	3350 / 40
Payload in kg at kph (2)	3350 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	160,8
Tyre content 75% [litre]	464
Stud width [mm]	48
Stud height [mm]	51,0
Number of studs	21x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.