



#### Hints and features:

- The Michelin Cerexbib is a newly-developed tyre for large harvesting machines
- Due to its large contact area, the soil is optimally protected
- All Cerexbib tyres are CFO tyres for cyclic field operations
- The Cerexbib has a special casing construction with Ultraflex technology
- This casing structure enables higher loading capacities at the same inflation pressure (IF=up to 20%, VF=up to 40%)

REIFEN IF 680 / 85 R 32 CFO  
179 A8, TL, CEREXBIB

**Product-No.: 13327018**

#### Technical Information:

Tyre size	IF 680 / 85 R 32 CFO
TL / TT	TL
LI / SI	179 A8
Tread	CerexBib
Manufacturer	Michelin
Recom. Rim	23
Permissible rim	21
Width [mm]	682
Outer diameter [mm]	1969
Static radius [mm]	861
Rolling circumference [mm]	5819
Payload in kg at kph (1)	7750 / 40
Inflation pressure [bar]	2,40
Weight [Kg]	302
Tyre content 75% [litre]	859
Stud height [mm]	46,0
Number of studs	18x2
Zulassung	nicht notwendig
Cyclic field use	CFO
Tyre technology	IF
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.