



REIFEN 440 / 80 R 24
161 A8 / 161 B, TL, XMCL
(16.9 R 24)

Product-No.: 13327376

Technical Information:

Tyre size	440 / 80 R 24
TL / TT	TL
LI / SI	161 A8 / 161 B
Tread	XMCL
Manufacturer	Michelin
Recom. Rim	14
Permissible rim	15
Width [mm]	441
Outer diameter [mm]	1314
Static radius [mm]	592
Rolling circumference [mm]	3907
Payload in kg at kph (1)	4625 / 40
Payload in kg at kph (2)	4625 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	115
Tyre content 75% [litre]	236
Stud height [mm]	36,0
Number of studs	20x2
Zulassung	nicht notwendig
Direction bound	Yes

Hints and features:

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers
- Reinforced sidewalls
- Solid lugs
- Belt plies made from steel mesh

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.