



REIFEN 280 / 80 - 18  
132 A8, TL, POWER CL  
(10.5/80 - 18)

**Product-No.: 13371010**

#### Technical Information:

|                            |                 |
|----------------------------|-----------------|
| Tyre size                  | 280 / 80 - 18   |
| TL / TT                    | TL              |
| LI / SI                    | 132 A8          |
| Tread                      | Power CL        |
| Manufacturer               | Michelin        |
| Recom. Rim                 | 9               |
| Permissible rim            | 8, 10           |
| Width [mm]                 | 288             |
| Outer diameter [mm]        | 902             |
| Static radius [mm]         | 413             |
| Rolling circumference [mm] | 2691            |
| Payload in kg at kph (1)   | 2000 / 40       |
| Inflation pressure [bar]   | 4,00            |
| Weight [Kg]                | 38              |
| Tyre content 75% [litre]   | 80              |
| Stud height [mm]           | 26,0            |
| Number of studs            | 19x2            |
| Zulassung                  | nicht notwendig |
| Direction bound            | Yes             |

#### Hints and features:

- Industrial tyre for wheel loaders, backhoe loaders and telescopic handlers
- Solid lugs and abrasion-resistant rubber compound
- Extreme lateral stability due to casing plies

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.