



REIFEN 320 / 85 R 28
124 A8 / 121 B, TL, TM 600

Product-No.: 13626255

Technical Information:

Tyre size	320 / 85 R 28
TL / TT	TL
LI / SI	124 A8 / 121 B
Tread	TM600
Manufacturer	Trelleborg
Recom. Rim	11
Permissible rim	9, 10
Width [mm]	329
Outer diameter [mm]	1255
Static radius [mm]	566
Rolling circumference [mm]	3796
Payload in kg at kph (1)	1600 / 40
Payload in kg at kph (2)	1450 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	57,26
Tyre content 75% [litre]	157
Stud width [mm]	34
Stud height [mm]	41,0
Number of studs	21x2
Zulassung	nicht notwendig
Direction bound	Yes

Hints and features:

- Protects turf and crops due to innovative tread pattern
- High load capacity
- Low soil compaction
- Optimal traction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.