



REIFEN 600 / 70 R 28
157 D / 154 E, TL, TM 900 HP

Product-No.: 13626333

Technical Information:

Tyre size	600 / 70 R 28
TL / TT	TL
LI / SI	157 D / 154 E
Tread	TM900HP
Manufacturer	Trelleborg
Recom. Rim	18
Permissible rim	20
Width [mm]	604
Outer diameter [mm]	1551
Static radius [mm]	699
Rolling circumference [mm]	4720
Payload in kg at kph (1)	4125 / 65
Payload in kg at kph (2)	3750 / 70
Inflation pressure [bar]	2,40
Weight [Kg]	184
Zulassung	nicht notwendig
Direction bound	Yes

Hints and features:

- The TM 900 High Power was developed specifically for the biggest agricultural machines and high-performance tractors
- It offers extremely high load capacity
- Due to its special design, the tyre transmits the vehicle's high torque and enables high traction on all soils
- It is characterised through extraordinarily high ride comfort and safety

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes
Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.