



■ ■ ● Bohnenkamp

REIFEN 540 / 65 R 30  
143 D, TL, TM 800

**Product-No.: 13626353**

#### Technical Information:

Tyre size	540 / 65 R 30
TL / TT	TL
LI / SI	143 D
Tread	TM800
Manufacturer	Trelleborg
Recom. Rim	16
Permissible rim	15, 18
Width [mm]	530
Outer diameter [mm]	1464
Static radius [mm]	665
Rolling circumference [mm]	4400
Payload in kg at kph (1)	2725 / 65
Inflation pressure [bar]	1,60
Weight [Kg]	128,62
Tyre content 75% [litre]	385
Stud width [mm]	55
Stud height [mm]	50,0
Number of studs	21x2
Zulassung	nicht notwendig
Direction bound	Yes

#### Hints and features:

- Modern agricultural tyre, approved up to 65 km/h
- Maximum performance in the field due to extra-large contact area
- High level of comfort
- Long service life

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.