



■ ■ ● Bohnenkamp

REIFEN 540 / 65 R 34  
152 D / 149 E, TL, TM 800 HS

**Product-No.: 13626456**

#### Technical Information:

Tyre size	540 / 65 R 34
TL / TT	TL
LI / SI	152 D / 149 E
Tread	TM800
Manufacturer	Trelleborg
Specification	High Speed
Recom. Rim	16
Permissible rim	15, 18
Width [mm]	530
Outer diameter [mm]	1566
Static radius [mm]	710
Rolling circumference [mm]	4710
Payload in kg at kph (1)	3550 / 65
Payload in kg at kph (2)	3250 / 70
Inflation pressure [bar]	2,40
Weight [Kg]	144,97
Stud width [mm]	38
Stud height [mm]	50,0
Zulassung	nicht notwendig
Direction bound	Yes

#### Hints and features:

- Wide radial tractor tyre of the 65 series for high-performance tractors of approximately 100-220 hp
- Suitable for the heaviest farm work and frequent road use
- Approved for 70 km/h and increased loading capacity compared with the TM 800
- Large contact area ensures that more lugs interlock with the ground and thus improve traction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.