



REIFEN 650 / 75 R 38
169 D / 166 E, TL, TM 900 HP

Product-No.: 13626640

Technical Information:

Tyre size	650 / 75 R 38
TL / TT	TL
LI / SI	169 D / 166 E
Tread	TM900HP
Manufacturer	Trelleborg
Recom. Rim	23
Width [mm]	676
Outer diameter [mm]	1940
Static radius [mm]	855
Rolling circumference [mm]	5840
Payload in kg at kph (1)	5800 / 65
Payload in kg at kph (2)	5300 / 70
Inflation pressure [bar]	2,40
Weight [Kg]	281
Zulassung	nicht notwendig
Direction bound	Yes

Hints and features:

- The TM 900 High Power was developed specifically for the biggest agricultural machines and high-performance tractors
- It offers extremely high load capacity
- Due to its special design, the tyre transmits the vehicle's high torque and enables high traction on all soils
- It is characterised through extraordinarily high ride comfort and safety

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes
Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.