



Hints and features:

- The Alliance Forestar 344 is a powerful forestry tyre for CTL machines
- The steel-reinforced nylon casing, the special rubber compound, as well as the reinforced sidewalls, protect the tyre against punctures
- The traction tread pattern with low-angled lugs provides excellent grip and good self-cleaning thanks to wide gaps between the lugs
- Due to the close spacing of the lugs in the centre of the tread, the rolling resistance can be reduced on hard surfaces
- Matching chains and ribbons are available on the market

REIFEN 710 / 40 - 22.5

16 PR, 161 A2 / 154 A8, TL, FORESTAR 344, LS-2
ECE106

Product-No.: 15212662

Technical Information:

Tyre size	710 / 40 - 22.5
TL / TT	TL
LI / SI	161 A2 / 154 A8
PR	16
Tread	Forestar 344
Manufacturer	Alliance
Specification	LS-2
Recom. Rim	24.00
Width [mm]	700
Outer diameter [mm]	1170
Static radius [mm]	540
Rolling circumference [mm]	3502
Payload in kg at kph (1)	4625 / 10
Payload in kg at kph (2)	3750 / 40
Inflation pressure [bar]	3,60
Weight [Kg]	163,08
Stud height [mm]	51,0
Zulassung	ECE 106
TRA Code	LS-2