# Bohnenkamp Moving Professionals

## 



#### Hints and features:

- Ideal for longer transport and grassland use
- Block tread for smooth handling on long road journeys and ground protection during grassland use
- Low rolling resistance for minimum fuel consumption
- High tread depth for a long service lifespan
- Steel belt reinforcement for high load capacities and improved stability

## REIFEN 30.5 L R 32 181 B, TL, 390 STEEL BELTED, ECE106

### Product-No.: 15215830

#### **Technical Information:**

Tyre size	30.5L R 32
TL / TT	TL
LI / SI	181 B
Tread	390
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	27
Width [mm]	790
Outer diameter [mm]	1800
Static radius [mm]	805
Rolling circumference [mm]	5431
Payload in kg at kph (1)	8250 / 50
Inflation pressure [bar]	3,00
Weight [Kg]	272,64
Tyre content 75% [litre]	1.073
Stud height [mm]	30,0
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.