



REIFEN 17.5 L - 24
10 PR, 144 A8, TL, 533
ECE106

Product-No.: 15222280

Technical Information:

Tyre size	17.5 L - 24
TL / TT	TL
LI / SI	144 A8
PR	10
Tread	533
Manufacturer	Alliance
Recom. Rim	W15L
Permissible rim	W14L
Width [mm]	444
Outer diameter [mm]	1240
Static radius [mm]	551
Rolling circumference [mm]	3623
Payload in kg at kph (1)	2800 / 40
Inflation pressure [bar]	2,20
Weight [Kg]	70,4
Stud height [mm]	25,0
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- The Alliance 533 is an industrial and construction tyre for wheel loaders and backhoes
- Its strong nylon casing offers the best conditions for off-road use on construction sites
- Its tread pattern provides good traction, braking power and high mileage when used on roads
- The tyre can also be used on municipal tractors and agricultural vehicles

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.