



Hints and features:

- Row crop tyre for use on tractors and self-propelled field sprayers
- Ideal for crop protection and maintenance work on row crops
- Rounded shoulders protect against plant and soil damage
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank)
- 65 km/h approval (subject to exceptions)

REIFEN 380 / 90 R 54
174 A8 / 171 D, TL, 350
(14.9R54), ECE106

Product-No.: 15226723

Technical Information:

Tyre size	380 / 90 R 54
TL / TT	TL
LI / SI	174 A8 / 171 D
Tread	350
Manufacturer	Alliance
Recom. Rim	12
Permissible rim	11, 13
Width [mm]	388
Outer diameter [mm]	2055
Static radius [mm]	962
Rolling circumference [mm]	6257
Payload in kg at kph (1)	6700 / 40
Payload in kg at kph (2)	6150 / 65
Inflation pressure [bar]	4,80
Weight [Kg]	160,63
Tyre content 75% [litre]	338
Stud height [mm]	47,0
Number of studs	35x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.