



REIFEN 600 / 65 R 38  
162 A8 / 159 D, TL, AGRISTAR 365  
ECE106

**Product-No.: 15226788**

#### Technical Information:

Tyre size	600 / 65 R 38
TL / TT	TL
LI / SI	162 A8 / 159 D
Tread	Agristar 365
Manufacturer	Alliance
Recom. Rim	DW20B
Permissible rim	DW18
Width [mm]	594
Outer diameter [mm]	1.745
Static radius [mm]	782
Rolling circumference [mm]	5284
Payload in kg at kph (1)	4750 / 40
Payload in kg at kph (2)	4375 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	181,16
Tyre content 75% [litre]	478
Stud width [mm]	46-49
Stud height [mm]	49,0
Zulassung	ECE 106
Direction bound	Yes

#### Hints and features:

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp
- Very gentle tillage due to high air volume and large contact area
- Lug shape and arrangement allows optimum traction power distribution
- With 65 km/h approval, suitable for frequent road use

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.