



REIFEN 460 / 70 R 24
159 A8 / 159 B, TL, MULTIUSE 550, M+S
STEEL BELTED, BLOCK PROFIL (17.5 LR 24),
ECE106

Product-No.: 15284048

Technical Information:

Tyre size	460 / 70 R 24
TL / TT	TL
LI / SI	159 A8 / 159 B
Tread	Multiuse 550
Manufacturer	Alliance
Specification	M+S, Steel Belted
Recom. Rim	15
Permissible rim	14, 16
Width [mm]	460
Outer diameter [mm]	1250
Static radius [mm]	568
Rolling circumference [mm]	3752
Payload in kg at kph (1)	4375 / 40
Payload in kg at kph (2)	4375 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	99,93
Tyre content 75% [litre]	217,5
Stud height [mm]	25,0
Zulassung	ECE 106
M+S	M+S

Hints and features:

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres
- Steel belt reinforcement for high load capacity and protection against punctures
- With M+S identification