



REIFEN 405 / 70 R 20
155 A2 / 143 B, TL, 608
STEEL BELTED (16.0/70R20), ECE106

Product-No.: 15284920

Technical Information:

Tyre size	405 / 70 R 20
TL / TT	TL
LI / SI	155 A2 / 143 B
Tread	608
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	13
Permissible rim	11, 12, 14
Width [mm]	407
Outer diameter [mm]	1076
Static radius [mm]	470
Rolling circumference [mm]	3247
Payload in kg at kph (1)	3875 / 10
Payload in kg at kph (2)	2725 / 50
Inflation pressure [bar]	3,75
Weight [Kg]	60,59
Tyre content 75% [litre]	141
Stud height [mm]	18,5
Number of studs	25x2
Zulassung	ECE 106

Hints and features:

- MPT radial tyre for compact construction machinery, such as excavators, wheel or telescopic loaders and skid steer machines
- Massive contact area for stability, in combination with wide centre lugs for hard surfaces
- High lugs in the shoulder area for traction on loose surfaces
- Optimised rolling resistance allows fuel savings

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.