Bohnenkamp Moving Professionals





Hints and features:

- Grass tyre with excellent contact area for low soil compaction
- Rounded tyre shoulder for optimal turf protection
- High tread pattern depth in conjunction with a rugged casing for high mileage and protection against damage (punctures)

REIFEN 13.6 - 16 4 PR, 106 A3 / 102 A6, TL, LG 306, RASENPROFIL ECE106

Product-No.: 15710575

Technical Information:

Tyre size	13.6 - 16
TL/TT	TL
LI / SI	106 A3 / 102 A6
PR	4
Tread	LG 306
Manufacturer	ВКТ
Recom. Rim	W12
Permissible rim	W11
Width [mm]	388
Outer diameter [mm]	975
Static radius [mm]	439
Rolling circumference [mm]	2793
Payload in kg at kph (1)	950 / 15
Payload in kg at kph (2)	850 / 30
Inflation pressure [bar]	1,00
Weight [Kg]	39,67
Stud height [mm]	19,0
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.