



REIFEN 6.5 / 80 - 12
6 PR, 80 A8 / 93 A8, TT, AS 504
ECE106

Product-No.: 15711280

Technical Information:

Tyre size	6.5 / 80 - 12
TL / TT	TT
LI / SI	80 A8 / 93 A8
PR	6
Tread	AS 504
Manufacturer	BKT
Recom. Rim	5J
Permissible rim	4.25, 5JA, 5.00
Width [mm]	163
Outer diameter [mm]	608
Static radius [mm]	273
Rolling circumference [mm]	1851
Payload in kg at kph (1)	450 / 40
Payload in kg at kph (2)	650 / 40
Inflation pressure [bar]	3,60
Weight [Kg]	7,54
Stud height [mm]	14,5
Number of studs	16x2
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.