



■ ■ ■ Bohnenkamp

REIFEN 8 - 16
6 PR, 91 A6 / 88 A8, TT, TR 144, AS
ECE106

Product-No.: 15711709

Technical Information:

Tyre size	8 - 16
TL / TT	TT
LI / SI	91 A6 / 88 A8
PR	6
Tread	TR 144
Manufacturer	BKT
Recom. Rim	6LB
Permissible rim	6.00F
Width [mm]	200
Outer diameter [mm]	785
Static radius [mm]	358
Rolling circumference [mm]	2342
Payload in kg at kph (1)	615 / 30
Payload in kg at kph (2)	560 / 40
Inflation pressure [bar]	1,90
Weight [Kg]	14,88
Stud height [mm]	27,0
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- Agricultural bias tyre for smaller tractors
- Wide lug spaces for good traction on wet surfaces
- Angled lugs in the centre for better ride comfort

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.