



■ ■ ● Bohnenkamp



REIFEN 12.5 / 80 - 15.3
14 PR, 142 A8, TL, AW 702
ECE106

Product-No.: 15711800

Technical Information:

Tyre size	12.5 / 80 - 15.3
TL / TT	TL
LI / SI	142 A8
PR	14
Tread	AW 702
Manufacturer	BKT
Recom. Rim	9.00
Permissible rim	11.00
Width [mm]	312
Outer diameter [mm]	885
Static radius [mm]	387
Rolling circumference [mm]	2593
Payload in kg at kph (1)	2650 / 40
Inflation pressure [bar]	4,30
Weight [Kg]	28,3
Stud height [mm]	12,0
Zulassung	ECE 106

Hints and features:

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.