





Hints and features:

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

REIFEN 15.0 / 55 - 17 18 PR, 146 A8, TL, AW 705 ECE106

Product-No.: 15711848

Technical Information:

Tyre size	15.0 / 55 - 17
TL / TT	TL
LI/SI	146 A8
PR	18
Tread	AW 705
Manufacturer	BKT
Recom. Rim	13.00
Width [mm]	381
Outer diameter [mm]	850
Static radius [mm]	391
Rolling circumference [mm]	2575
Payload in kg at kph (1)	3000 / 40
Payload in kg at kph (2)	2060 / 40
Inflation pressure [bar]	4,70
Weight [Kg]	34,22
Stud height [mm]	12,0
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.