



REIFEN 500 / 45 - 22.5

16 PR, 142 A8 / 154 A8, TL, FLOTATION 558
ECE106

Product-No.: 15712515

Technical Information:

Tyre size	500 / 45 - 22.5
TL / TT	TL
LI / SI	142 A8 / 154 A8
PR	16
Tread	Flotation 558
Manufacturer	BKT
Recom. Rim	AG16.00
Width [mm]	500
Outer diameter [mm]	1045
Static radius [mm]	471
Rolling circumference [mm]	3167
Payload in kg at kph (1)	2650 / 40
Payload in kg at kph (2)	3750 / 40
Inflation pressure [bar]	3,60
Weight [Kg]	60,52
Stud height [mm]	19,0
Number of studs	26x2
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- Flotation tyre for high payloads with low inflation pressure
- Suitable for road and field use
- Minimal soil compaction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.