



Hints and features:

- The BKT Flotation TR 675 is particularly suitable for soil tillage and transport operations
- It can be used on trailers, compact dumpers and implements
- The tyre provides outstanding traction while protecting the soil

REIFEN 500 / 60 - 22.5

16 PR, 151 A8 / 163 A8, TL, FLOTATION TR 675
ECE106

Product-No.: 15712528

Technical Information:

Tyre size	500 / 60 - 22.5
TL / TT	TL
LI / SI	151 A8 / 163 A8
PR	16
Tread	Flotation TR 675
Manufacturer	BKT
Recom. Rim	AG16.00
Permissible rim	15.00, 17.00
Width [mm]	500
Outer diameter [mm]	1181
Static radius [mm]	534
Rolling circumference [mm]	3505
Payload in kg at kph (1)	3450 / 40
Payload in kg at kph (2)	4875 / 40
Inflation pressure [bar]	4,40
Weight [Kg]	94,24
Stud height [mm]	38,0
Number of studs	17x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.