# Bohnenkamp Moving Professionals



### Hints and features:

- Suitable for timber harvesting machines and tow tractors
- Rugged casing guarantees high load capacity
- Reinforced bead and lug area for a long service life

## REIFEN 710 / 45 - 26.5 20 PR, 175 A2 / 168 A8, TL, FORESTECH ECE106

## Product-No.: 15712860

### **Technical Information:**

Tyre size	710 / 45 - 26.5
TL/TT	TL
LI / SI	175 A2 / 168 A8
PR	20
Tread	Forestech
Manufacturer	ВКТ
Specification	LS-2
Recom. Rim	24.00
Width [mm]	710
Outer diameter [mm]	1340
Static radius [mm]	620
Rolling circumference [mm]	4047
Payload in kg at kph (1)	6900 / 10
Payload in kg at kph (2)	5600 / 40
Inflation pressure [bar]	5,00
Weight [Kg]	225,24
Stud height [mm]	32,0
Number of studs	18x2
Zulassung	ECE 106
TRA Code	LS-2

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential

damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.