



REIFEN 8.3 - 24
6 PR, 100 A6 / 96 A8, TT, TR 135, AS
ECE106

Product-No.: 15722090

Technical Information:

| | |
|----------------------------|----------------|
| Tyre size | 8.3 - 24 |
| TL / TT | TT |
| LI / SI | 100 A6 / 96 A8 |
| PR | 6 |
| Tread | TR 135 |
| Manufacturer | BKT |
| Recom. Rim | W7 |
| Permissible rim | W6 |
| Width [mm] | 211 |
| Outer diameter [mm] | 995 |
| Static radius [mm] | 469 |
| Rolling circumference [mm] | 2985 |
| Payload in kg at kph (1) | 800 / 30 |
| Payload in kg at kph (2) | 710 / 40 |
| Inflation pressure [bar] | 2,40 |
| Weight [Kg] | 19,77 |
| Stud height [mm] | 28,0 |
| Number of studs | 21x2 |
| Zulassung | ECE 106 |
| Direction bound | Yes |

Hints and features:

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications
- Some sizes and versions are suitable for use on excavators, trailers or harvesters
- The double angled lugs provide excellent traction
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions
- The lugs overlapping in the tread centre ensure comfortable handling on the road