



REIFEN 13.6 - 24
8 PR, 123 A6 / 120 A8, TT, TR 135, AS
ECE106

Product-No.: 15722170

Technical Information:

Tyre size	13.6 - 24
TL / TT	TT
LI / SI	123 A6 / 120 A8
PR	8
Tread	TR 135
Manufacturer	BKT
Recom. Rim	W12
Permissible rim	W11
Width [mm]	355
Outer diameter [mm]	1220
Static radius [mm]	562
Rolling circumference [mm]	3698
Payload in kg at kph (1)	1550 / 30
Payload in kg at kph (2)	1400 / 40
Inflation pressure [bar]	2,00
Weight [Kg]	46,32
Stud width [mm]	36
Stud height [mm]	36,0
Number of studs	17x2
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- The BKT TR 135 is an agricultural bias tyre for soil tillage and spraying applications
- Some sizes and versions are suitable for use on excavators, trailers or harvesters
- The double angled lugs provide excellent traction
- The tyre offers good self-cleaning properties and excellent stability, even on difficult ground conditions
- The lugs overlapping in the tread centre ensure comfortable handling on the road

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.