



## Hints and features:

- For log skidders and skidders
- Rugged lug design for very good traction
- Steel belt construction with nylon casing to protect against punctures
- Reinforced sidewall and bead protection

REIFEN 30.5 L - 32  
16 PR, 166 A6, TL, FS 216, LS-2  
ECE106

**Product-No.: 15722580**

## Technical Information:

Tyre size	30.5L - 32
TL / TT	TL
LI / SI	166 A6
PR	16
Tread	FS 216
Manufacturer	BKT
Specification	LS-2
Recom. Rim	DH27
Permissible rim	DH27B
Width [mm]	775
Outer diameter [mm]	1847
Static radius [mm]	833
Rolling circumference [mm]	5466
Payload in kg at kph (1)	5300 / 30
Inflation pressure [bar]	1,70
Weight [Kg]	448,02
Stud height [mm]	58,0
Number of studs	16x2
Zulassung	ECE 106
Direction bound	Yes
TRA Code	LS-2

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.