# Bohnenkamp Moving Professionals

BKT



#### Hints and features:

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp
- Large choice of dimensions, may also be used as a row crop tyre
- Good traction and self-cleaning
- Rounded lugs in the shoulder area for plant protection
- Optimised rubber compound: 25 % less wear, 30 % improved resistance to cuts and shedding, 20% more traction

## REIFEN 380 / 85 R 24 131 A8 / 131 B, TL, AGRIMAX RT 855 (14.9 R 24), ECE106

## Product-No.: 15726120

### **Technical Information:**

Tyre size	380 / 85 R 24
TL / TT	TL
LI / SI	131 A8 / 131 B
Tread	Agrimax RT 855
Manufacturer	ВКТ
Recom. Rim	W12
Permissible rim	W11, W13
Width [mm]	380
Outer diameter [mm]	1256
Static radius [mm]	554
Rolling circumference [mm]	3720
Payload in kg at kph (1)	1950 / 40
Payload in kg at kph (2)	1950 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	73,5
Tyre content 75% [litre]	174
Stud width [mm]	34
Stud height [mm]	45,0
Number of studs	18x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.