



■ ■ ■ Bohnenkamp

REIFEN 340 / 85 R 28  
127 A8 / 127 B, TL, AGRIMAX RT 855  
(13.6 R 28), ECE106

**Product-No.: 15726180**

#### Technical Information:

Tyre size	340 / 85 R 28
TL / TT	TL
LI / SI	127 A8 / 127 B
Tread	Agrimax RT 855
Manufacturer	BKT
Recom. Rim	12
Permissible rim	11
Width [mm]	353
Outer diameter [mm]	1289
Static radius [mm]	588
Rolling circumference [mm]	3890
Payload in kg at kph (1)	1750 / 40
Payload in kg at kph (2)	1750 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	67,97
Tyre content 75% [litre]	147
Stud width [mm]	33
Stud height [mm]	44,0
Number of studs	19x2
Zulassung	ECE 106
Direction bound	Yes

#### Hints and features:

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp
- Large choice of dimensions, may also be used as a row crop tyre
- Good traction and self-cleaning
- Rounded lugs in the shoulder area for plant protection
- Optimised rubber compound: 25 % less wear, 30 % improved resistance to cuts and shedding, 20% more traction