



REIFEN 420 / 85 R 28
139 A8 / 139 B, TL, AGRIMAX RT 855
(16.9 R 28), ECE106

Product-No.: 15726200

Technical Information:

Tyre size	420 / 85 R 28
TL / TT	TL
LI / SI	139 A8 / 139 B
Tread	Agrimax RT 855
Manufacturer	BKT
Recom. Rim	15
Permissible rim	13, 14
Width [mm]	438
Outer diameter [mm]	1425
Static radius [mm]	638
Rolling circumference [mm]	4241
Payload in kg at kph (1)	2430 / 40
Payload in kg at kph (2)	2430 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	103,27
Tyre content 75% [litre]	246,75
Stud width [mm]	36
Stud height [mm]	49,0
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp
- Large choice of dimensions, may also be used as a row crop tyre
- Good traction and self-cleaning
- Rounded lugs in the shoulder area for plant protection
- Optimised rubber compound: 25 % less wear, 30 % improved resistance to cuts and shedding, 20% more traction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.