



REIFEN 460 / 85 R 38  
149 A8 / 149 B, TL, AGRIMAX RT 855  
(18.4R38), ECE106

**Product-No.: 15726400**

#### Technical Information:

Tyre size	460 / 85 R 38
TL / TT	TL
LI / SI	149 A8 / 149 B
Tread	Agrimax RT 855
Manufacturer	BKT
Recom. Rim	W16L
Permissible rim	W14L, W15L
Width [mm]	475
Outer diameter [mm]	1747
Static radius [mm]	785
Rolling circumference [mm]	5205
Payload in kg at kph (1)	3250 / 40
Payload in kg at kph (2)	3250 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	147,67
Tyre content 75% [litre]	390
Stud width [mm]	42
Stud height [mm]	54,0
Number of studs	21x2
Zulassung	ECE 106
Direction bound	Yes

#### Hints and features:

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp
- Large choice of dimensions, may also be used as a row crop tyre
- Good traction and self-cleaning
- Rounded lugs in the shoulder area for plant protection
- Optimised rubber compound: 25 % less wear, 30 % improved resistance to cuts and shedding, 20% more traction