



REIFEN 520 / 85 R 38  
170 A8 / 170 B, TL, AGRIMAX RT 855  
(20.8 R 38), ECE106

**Product-No.: 15726412**

#### Technical Information:

Tyre size	520 / 85 R 38
TL / TT	TL
LI / SI	170 A8 / 170 B
Tread	Agrimax RT 855
Manufacturer	BKT
Specification	R1-W
Recom. Rim	DW16L
Permissible rim	DW18L, DD16L
Width [mm]	516
Outer diameter [mm]	1849
Static radius [mm]	847
Rolling circumference [mm]	5595
Payload in kg at kph (1)	6000 / 40
Payload in kg at kph (2)	6000 / 50
Inflation pressure [bar]	3,60
Weight [Kg]	201,57
Tyre content 75% [litre]	516,75
Stud height [mm]	57,0
Number of studs	21x2
Zulassung	ECE 106
Direction bound	Yes
TRA Code	R1-W

#### Hints and features:

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp
- Large choice of dimensions, may also be used as a row crop tyre
- Good traction and self-cleaning
- Rounded lugs in the shoulder area for plant protection
- Optimised rubber compound: 25 % less wear, 30 % improved resistance to cuts and shedding, 20% more traction