



REIFEN 200 / 70 R 16  
94 A8 / 94 B, TL, AGRIMAX RT 765  
ECE106

**Product-No.: 15726540**

#### Technical Information:

Tyre size	200 / 70 R 16
TL / TT	TL
LI / SI	94 A8 / 94 B
Tread	Agrimax RT 765
Manufacturer	BKT
Recom. Rim	W6
Permissible rim	7.0
Width [mm]	197
Outer diameter [mm]	686
Static radius [mm]	313
Rolling circumference [mm]	2037
Payload in kg at kph (1)	670 / 40
Payload in kg at kph (2)	670 / 50
Inflation pressure [bar]	2,40
Weight [Kg]	16
Tyre content 75% [litre]	20,25
Stud height [mm]	26,0
Number of studs	18x2
Zulassung	ECE 106
Direction bound	Yes

#### Hints and features:

- Wide-base tyre of the 70 series for tractors in the low- to medium-power range.
- Principal areas of use: arable farming and grassland
- Low soil compaction and good self-cleaning properties
- Optimised rubber compound: 25 % less wear, 30 % improved resistance to cuts and shedding, 20% more traction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.