



Hints and features:

- Super-wide tyre for high-performance tractors from approx. 200 hp
- High load capacity in combination with excellent traction due to extended contact area and sturdy lugs
- Efficient in field operations, improved transport performance with excellent ride comfort and lower rolling resistance
- Reduction in operating costs through fuel savings and high mileage

REIFEN 600 / 70 R 34 163 A8 / 160 D, TL, AGRIMAX FORTIS ECE106

Product-No.: 15726850

Technical Information:

Tyre size	600 / 70 R 34
TL/TT	TL
LI/SI	163 A8 / 160 D
Tread	Agrimax Fortis
Manufacturer	BKT
Recom. Rim	DW18L
Permissible rim	DW20B, W18L
Width [mm]	591
Outer diameter [mm]	1704
Static radius [mm]	761
Rolling circumference [mm]	5109
Payload in kg at kph (1)	4875 / 40
Payload in kg at kph (2)	4500 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	193,92
Stud height [mm]	58,0
Number of studs	20x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.