



REIFEN 540 / 65 R 24
149 A8 / 146 D, TL, AGRIMAX RT 657
ECE106

Product-No.: 15727060

Technical Information:

Tyre size	540 / 65 R 24
TL / TT	TL
LI / SI	149 A8 / 146 D
Tread	Agrimax RT 657
Manufacturer	BKT
Recom. Rim	W16L
Permissible rim	W18L
Width [mm]	530
Outer diameter [mm]	1312
Static radius [mm]	590
Rolling circumference [mm]	3930
Payload in kg at kph (1)	3250 / 40
Payload in kg at kph (2)	3000 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	114,5
Stud width [mm]	40
Stud height [mm]	50,0
Number of studs	18x2
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption
- For road transport, the tyre is approved for speeds up to 65 km/h