





Hints and features:

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption
- For road transport, the tyre is approved for speeds up to 65 km/h

REIFEN 480 / 65 R 28 145 A8 / 142 D, TL, AGRIMAX RT 657 ECE106

Product-No.: 15727090

Technical Information:

Tyre size	480 / 65 R 28
TL/TT	TL
LI/SI	145 A8 / 142 D
Tread	Agrimax RT 657
Manufacturer	BKT
Recom. Rim	W15L
Permissible rim	W14L
Width [mm]	479
Outer diameter [mm]	1335
Static radius [mm]	610
Rolling circumference [mm]	4091
Payload in kg at kph (1)	2900 / 40
Payload in kg at kph (2)	2650 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	105,05
Stud height [mm]	47,0
Number of studs	20x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.