



REIFEN 600 / 65 R 28  
157 A8 / 154 D, TL, AGRIMAX RT 657  
ECE106

**Product-No.: 15727115**

#### Technical Information:

Tyre size	600 / 65 R 28
TL / TT	TL
LI / SI	157 A8 / 154 D
Tread	Agrimax RT 657
Manufacturer	BKT
Recom. Rim	DW20B
Permissible rim	W18L
Width [mm]	611
Outer diameter [mm]	1491
Static radius [mm]	670
Rolling circumference [mm]	4470
Payload in kg at kph (1)	4125 / 40
Payload in kg at kph (2)	3750 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	156
Stud height [mm]	55,0
Number of studs	21x2
Zulassung	ECE 106
Direction bound	Yes

#### Hints and features:

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption
- For road transport, the tyre is approved for speeds up to 65 km/h