



REIFEN 600 / 65 R 38
162 A8 / 159 D, TL, AGRIMAX RT 657
ECE106

Product-No.: 15727185

Technical Information:

Tyre size	600 / 65 R 38
TL / TT	TL
LI / SI	162 A8 / 159 D
Tread	Agrimax RT 657
Manufacturer	BKT
Recom. Rim	DW20B
Permissible rim	W18L
Width [mm]	611
Outer diameter [mm]	1745
Static radius [mm]	790
Rolling circumference [mm]	5247
Payload in kg at kph (1)	4750 / 40
Payload in kg at kph (2)	4375 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	195,21
Stud width [mm]	46-47
Stud height [mm]	55,0
Number of studs	21x2
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption
- For road transport, the tyre is approved for speeds up to 65 km/h