



## Hints and features:

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- · Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

REIFEN 230 / 95 R 42 133 A8 / 133 B, TL, AGRIMAX RT 955 (9.5 R 42), ECE106

Product-No.: 15727480

## **Technical Information:**

Tyre size	230 / 95 R 42
TL / TT	TL
LI/SI	133 A8 / 133 B
Tread	Agrimax RT 955
Manufacturer	BKT
Recom. Rim	W8
Permissible rim	W7
Width [mm]	238
Outer diameter [mm]	1506
Static radius [mm]	714
Rolling circumference [mm]	4633
Payload in kg at kph (1)	2060 / 40
Payload in kg at kph (2)	2060 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	56,5
Stud height [mm]	33,0
Number of studs	34x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.