



Hints and features:

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- · Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

REIFEN 230 / 95 R 48 136 A8 / 136 B, TL, AGRIMAX RT 955 (9.5 R 48), ECE106

Product-No.: 15727596

Technical Information:

Tyre size	230 / 95 R 48
TL / TT	TL
LI / SI	136 A8 / 136 B
Tread	Agrimax RT 955
Manufacturer	BKT
Recom. Rim	W8
Permissible rim	W7
Width [mm]	238
Outer diameter [mm]	1656
Static radius [mm]	792
Rolling circumference [mm]	5085
Rolling circumference [mm] Payload in kg at kph (1)	5085 2240 / 40
Payload in kg at kph (1)	2240 / 40
Payload in kg at kph (1) Payload in kg at kph (2)	2240 / 40 2240 / 50
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar]	2240 / 40 2240 / 50 4,00
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg]	2240 / 40 2240 / 50 4,00 61,6
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Stud width [mm]	2240 / 40 2240 / 50 4,00 61,6 23
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Stud width [mm] Stud height [mm]	2240 / 40 2240 / 50 4,00 61,6 23 33,0

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.