



Hints and features:

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

RAD 10.0 / 75 - 15.3 BKT AW 702
10 PR, 123 A8, TL, 6/161/205, E2, ET -5
9.00 X 15.3, RAL9006 SILBER, INKL. SCHLAUCH

Product-No.: 59911310

Technical Information:

Wheel size	10.0 / 75 - 15.3
LI / PR	123 A8, 10 PR
Tread	AW 702
Manufacturer	BKT
Rim	9.00 x 15.3
Connection	6/161/205
Bolt hole execution	E2
Rim centering	BZ
ET	-5
Width [mm]	274
Outer diameter [mm]	760
Static radius [mm]	343
Rolling circumference [mm]	2227
Inflation pressure [bar]	3,90
Loadcapacity Tyre	1550 / 40
Loadcapacity Rim	2800 / 25
Loadcapacity compl. Wheel	1550 / 40
Tread depth [mm]	10,5
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	29,5

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.