



Hints and features:

- High-speed flotation tyre up to 100 km/h for use on agricultural trucks
- All-steel casing for high load capacity and optimum transport capacity on long distance routes
- Block tread pattern and high tread percentage for excellent ride comfort and reduced fuel consumption
- Perfect for use on trucks in transport chains and for delivery vehicles

RAD 600 / 50 R 22.5 ALLIANCE 382
164 J, TL, 10/281/335, A3, ET -50
20.00 X 22.5, RAL9006 SILBER, VS H, ALL
STEEL

Product-No.: 59913535

Technical Information:

Wheel size	600 / 50 R 22.5
LI / PR	164 J
Tread	382
Manufacturer	Alliance
Rim	AG 20.00 x 22.5 H2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
ET	-50
Width [mm]	600
Outer diameter [mm]	1170
Static radius [mm]	535
Rolling circumference [mm]	3587
Inflation pressure [bar]	6,50
Loadcapacity Tyre	5000 / 100
Loadcapacity Rim	5000 / 100
Loadcapacity compl. Wheel	5000 / 100
Tread depth [mm]	25,0
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	194,8