



#### Hints and features:

- Bias flotation tyre for towed vehicles
- Soil-protecting tread pattern
- Also for tractors (turf rolls)

RAD 800 / 45 - 26.5 ALLIANCE FLOTATION 328  
16 PR, 177 A8 / 173 B, TL, 10/281/335, A3, ET 0  
28.00 X 26.5 TH2, RAL9006 SILBER

**Product-No.: 59913985**

#### Technical Information:

Wheel size	800 / 45 - 26.5
LI / PR	164 A8 / 177 A8, 16 PR
Tread	Flotation 328
Manufacturer	Alliance
Rim	AG 28.00 x 26.5 TH2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
Width [mm]	800
Outer diameter [mm]	1393
Static radius [mm]	614
Rolling circumference [mm]	4050
Inflation pressure [bar]	2,20
Loadcapacity Tyre	5000 / 40
Loadcapacity Rim	9930 / 40
Loadcapacity compl. Wheel	7300 / 40
Tread depth [mm]	25,0
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	277,06

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.