



RAD 30.5 L R 32 BKT RIDEMAX FL 690
181 B, TL, 10/281/335, B3, ET -50
27 X 32, RAL9006 SILBER, STEEL BELTED

Product-No.: 59914351

Technical Information:

Wheel size	30.5L R 32
LI / PR	181 B
Tread	Ridemax FL 690
Manufacturer	BKT
Rim	TW 27 B x 32
Connection	10/281/335
Bolt hole execution	B3
Rim centering	BZ
ET	-50
Width [mm]	790
Outer diameter [mm]	1800
Static radius [mm]	806
Rolling circumference [mm]	5430
Inflation pressure [bar]	3,00
Loadcapacity Tyre	8250 / 50
Loadcapacity Rim	13300 / 40
Loadcapacity compl. Wheel	8250 / 50
Tread depth [mm]	31,0
Rim material	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	455,04

Hints and features:

- Suitable for manure spreaders, transfer vehicles and other towed agricultural vehicles with approx. 75 % road use
- Tread pattern design with low rolling resistance for low fuel consumption
- Rugged casing with steel belt reinforcement provides additional load capacity and protection against punctures

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.